

## Anker touch monitor (SKI A series)



<b>LED panel Size:</b>	<b>32"</b> (TM-SKI32A)	<b>43"</b> (TM-SKI43A)	<b>55"</b> (TM-SKI55A)	<b>65"</b> (TM-SKI65A)
<b>Active area (W x H mm):</b>	696 x 390	939 x 527	1208 x 678	142 x 802
<b>Case Dimension (mm):</b>	W: 767 H: 464 D: 75	W: 939 H: 528 D: 60	W: 1280 H: 751 D: 76	W: 1501 H: 875 D: 76
<b>Interface:</b>	Monitor only: HDMI x 1, VGA x 1, Other: Request by client PC: USB x4, LAN x 1			
<b>Color of the monitor:</b>	Silver / White / Black			
<b>Resolution:</b>	1920 x 1080 (Full HD), 16:9			
<b>Contrast ratio:</b>	2000:1 or above	<b>Brightness:</b>	300 cd/m2 or above	
<b>Response time:</b>	5 - 6.5 ms	<b>Viewing angle:</b>	170° /170° or above	
<b>Speaker:</b>	8W x 2	<b>Case Material:</b>	Metal	
<b>Touch parameter:</b>	<b>Infra Red Technology: 6 points touch</b> Scanning accuracy: 4096*4096 Touch objects: Finger, Lifetime: > 60 million times Driver: NO need, plug and play Surface hardness: Mohs 7 tempered glass, Optical Clarity : >92% transmission			
<b>Accessories:</b>	Included: Power Cord, Manual, Warranty card Option: Movable Cart, Wall mount, stand			
<b>System (option)</b>	Intel i3-i7 CPU (H81) 4-8GB RAM, 128GB SSD or above USB x4, LAN x 1, Preloaded Win. 7/10 Pro. 64 bits			

The above pictures and specification are for reference only and subject to change without prior notice